

CLS prefers to work with BiLock (new generation) a high security locking system with patented key.

Advantages of the Locking system

Interchangeable lock-plug for maximum flexibility. Locks can be fitted at the various manufacturers by means of a special test key without having to use the original keys.
























If a lock code has to be changed due to loss of a key or based on new procedures, cores and keys with a new code can be installed in the casino in seconds with a special Quick Change Core-key without having to dismantle and re-assemble the entire lock from the machine.

This unique system features an extra locking bar which works together with a movable trigger located in the key.



- Security** Locks only opened with the original key.
Restricted key cutting and key issuing.
All different Casinos have different keys.
One person controls all locks with one key only.
Different key-head-colors, indicate different levels of access
- Patent** Patented key, ensures that duplication is limited to authorised dealers
- Installation time** Lock size is based on lock-hole in slot-machine.
A variety of different lock types are available to suit all different types of slot machines, table equipment and accessory products.
- QCC** Interchangeable Quick Chance Cores represent major advantages for the casinos:
"Lock bodies" are installed into the machines by the manufacturer without original keys.
"Lock plugs" with original keys are sent directly to the casino which can be installed in seconds on site.
QCC minimizes lock installation time in the casino and provides additional security during the installation.
Changes in lock combinations can be made in seconds by replacing the lock-plug when e.g. a key is lost or personnel or procedures change.
- Service** Excellent after sales service from both dealer and factory.
- Technical specifications**
- Tamper resistant** A high level of pick resistance by means of a patented key system with false holes in pins to resist picking.
- Durability** Fewer moving parts and stronger keys ensure a higher durability.
- Simplicity** Easy use and minimum maintenance.
- Maintenance** Easy access to lock-plug saves time.
- Flexibility** Many combinations means large master key systems re-pinnable lock-plug gives the lock a "longer life", when new procedures "change the lock"
Minimum order quantity for custom-made locks when requested
- Compatibility** Standard cylinders can retrofit most hardware



					
1. SAM 3226 Q	2. APL 3226 QCP	3. Key	4. QCC key	5. Key	6. Key
					
7. A33279 QCP	8. A33259 QCP	9. A33899 QCP	10. A33279 DQCP	11. A33899 DQCP	12. A25213-8
					
13. Camlock+add on switch	14. C1411	15. C1410	16. C14A / C14B	17. A0159 QCP	18. A25211-8
					
19. A0311LQCP	20. A0311QCP	21. A0311DQCP	22. A0278 QCP	23. A0186 QCP	24. A:116PC50 / B: A0172 QCP

1. Nr. SAM 3226 Q **BiLock's "manufacturing-key or test-key"**;
Fits at all the locks (without the plug)

2. Nr. APL3226QCP
BiLock's high security Quick Change Cores or Plugs
with 2 sidebars.

3. **BiLock's New Generation**; patented key with coloured keyhead.

4. QCC key **BiLock's New Generation**; Quick Change Core key.

5. Key **Color coding**; for the new Generation BiLock key

6. Key **Color coding**; for the new Generation BiLock key

7. Nr. A33279 QCP
Cam lock 5/8"; 18,5 mm. left or right opening direction,
90 or 180 degrees opening.

8. Nr. A33259 QCP
Cam lock 7/8"; 22 mm. left or right opening direction,
90 or 180 degrees opening.

9. Nr. A33899 QCP
Cam lock 1-1/8"; 29 mm. left or right opening direction,
90 or 180 degrees opening.

10. Nr. A33279 DQCP
Cam lock 5/8"; 18,5 mm. left or right opening direction,
90 or 180 degree opening. Key removable in closed and open position

11. Nr. A33899 DQCP
Cam lock 1-1/8"; 29 mm. left or right opening direction,
90 or 180 degrees opening. Key removable in closed and open position

12. Nr. A25213-8
Euro profile knob cylinder; K0x35 mm

13. Camlock + add on switch
Add on switch; fits on all standard cam locks

14. Nr. C1411
Switch for cam lock; 90dgr. Right = off>on, 90 dgr Left = off>on

15. Nr. C1410 **Switch for cam lock**; 90 dgr. Right = off>on, or on>off

16. C14A: **Wire for switch** C1411 & C1410: length 50 mm
with 3 mm female and 6 mm male connector
C14B: **Connectors** for C1411 & C1410: Loose 3 mm female
connector to be crimped on machine wires.

17. Nr. A0159 QCP **Switch lock**; off>on, or on>off

18. Nr. A25211-8 **Euro Profile cilinder**; single 0x35 mm

19. Nr. A0311 LQCP
Cupboard lock; latch function, locks without use of the key

20. Nr. A0311 QCP
Cupboard lock; deadbolt function, key retained in open position

21. Nr. A0311 DQCP
Cupboard lock; deadbolt function, key removable in open position

22. Nr. A0278 QCP **Push Lock**; locks without use of key

23. Nr. A0186 QCP **Hook lock**; locks without use of key

24. A: Nr. 116PC50: Burgwaechter padlock for profile cilinder: Shackle 8 mm
B: Nr. A0172 QCP: BiLock padlock: Shackle 5,5 mm



CASINO LOCKING SYSTEMS

www.casinolock.com

1. Straight cam	2. Off Set Cam, hole in line	3. Off Set Cam hole across	4. Stop Plate	5. Small Nut	6. Big Nut
7. Spacer Collar	8. Anchor Plate	9. Anchor Plate	10. Spur Washer	11. Lock Washer	12. Lock Washer
13. Adaptor AD3286	14. Ring	15. Wing Lock 16 mm	16. Wing Lock 29 mm	17. Blind Cover	18. DOM adaptor
19. Packing Plate	20. Strike Plate	21. Shaft Collar	22. Cover Plate	23. Locking Plate	24. WD40 Lockspray

1. Straight Cam

A: CM301571 work.length 25,4 mm. D: CM301576 work.length 41,3 mm
 B: CM301578 work.length 28,6 mm E: CM301579 work.length 57,2 mm
 C: CM301574 work.length 31,8 mm

2. Offset Cam 7,5mm (A/B/C) 14mm (D), hole in line

A: CM301549 work.length 27,5 mm. C: CM301559 work.length 40,0 mm
 B: CM301555 work.length 35,0 mm D: CM301569 work.length 38,0 mm

3. Offset Cams 7,5 mm, hole across

A: CM301550 work.length 27,5 mm. C: CM301560 work.length 40,0 mm
 B: CM301556 work.length 35,0 mm

4. Stop Plate

A: PA30151; 90 dgr. C: PA30153; 90 dgr. Left + right
 B: PA30152; 180 dgr. (for switch C1411)

5. Small Nut

A: NU30153; normal small nut for camlock
 B: NU30152; low small nut for camlock

6. Big Nut; NU30151; big nut for camlock

7. Spacer Collar for Cam Lock

A: C2015; 1,5 mm D: C2070; 7,0 mm
 B: C2020; 2,0 mm E: C2105; 10,5 mm / C2122; 12,2 mm
 C: C2030; 3,0 mm

8. Anchor Plate; C3010; 40 x 40 mm for camlock at wooden door

9. Anchor Plate; C3015; 32 x 50 mm for camlock at wooden door

10. Spur Washer; C3020; 34 x 19 mm for camlock at wooden door (soft)

11. Lock Washer; C3030; 31 x 19 mm for camlock at metal door

12. Lock Washer;

A: NU3040; lock washer; for small nut of camlock
 B: NU3045; lock washer; 0,6 mm to adjust cam position
 C: NU3050; washer 1,2 mm to adjust cam position

13. Adaptor

AD3286; for camlock 1-1/8" (12 pin to 8 pin plug)

14. Ring

A: C3040; steel 34 x 19 mm
 B: C3045; stainless steel 30 x 19 mm

15. Winglock 16 mm

16. Winglock 29 mm

17. Blind Cover

C3060; to cover the hole of a cam lock

18. Dom Adaptor

C3050; to change a DOM cam to a standard cam

19. Packing Plate

C4010; 1,5 mm for cupboard lock

20. Strike Plate;

C4020; cam locks & cupboard locks

21. Shaft Collar;

A: C4030 shaft collar; normal collar for push locks & cupboard locks
 B: C4035 shaft collar; high collar for cupboard locks (doors > 24,0 mm)

22. Cover Plate;

C4040; 65 x 65 mm, for cupboard locks

23. Locking Plate;

A: C4050 locking plate; for hook lock, gold plated
 B: C4055 locking plate; for hook lock, chrome

24. Lock Spray; C4060; special spray for locks and lock plugs

